

○リング寸法表 (V 番)

固定用 G番"O"リング(JIS B 2401)						
呼び番	呼び寸法		実寸法			
	d	D	W		d	
G25	25	30	5.7	±0.1	24.4	±0.15
G30	30	35			29.4	
G35	35	40			34.4	
G40	40	45			39.4	
G45	45	50			44.4	±0.25
G50	50	55			49.4	
G55	55	60			54.4	
G60	60	65			59.4	
G65	65	70			64.4	±0.4
G70	70	75			69.4	
G75	75	80			74.4	
G80	80	85			79.4	
G85	85	90			84.4	±0.6
G90	90	95			89.4	
G95	95	100			94.4	
G100	100	105	99.4			
G105	105	110	104.4	±0.8		
G110	110	115	109.4			
G115	115	120	114.4			
G120	120	125	119.4			
G125	125	130	124.4	±0.6		
G130	130	135	129.4			
G135	135	140	134.4			

呼び番	呼び寸法		実寸法				
	d	D	W		d		
G140	140	145	5.7	±0.1	139.4	±0.6	
G145	145	150			144.4		
G150	150	160	5.7	±0.15	149.3		±0.8
G155	155	165			154.3		
G160	160	170			159.3		
G165	165	175			164.3		
G170	170	180			169.3		
G175	175	185			174.3		
G180	180	190			179.3	±0.8	
G185	185	295			184.3		
G190	190	200			189.3		
G195	195	205			194.3		
G200	200	210	5.7	±0.15	199.3	±0.8	
G210	210	220			209.3		
G220	220	230			219.3		
G230	230	240			229.3		
G240	240	250			239.3		
G250	250	260			249.3		
G260	260	270			259.3		
G270	270	280			269.3		
G280	280	290			279.3		
G290	290	300			289.3		
G300	300	310	299.3				